

(11)Publication number:

03-209016

(43) Date of publication of application: 12.09.1991

(51)Int.CI.

F16C 19/52 G01L 1/00

(21)Application number: 02-330946

(71)Applicant: SKF NOVA AB

(22)Date of filing:

30.11.1990

(72)Inventor: ADOLFSSON RUNE

ASBERG STURE

HESTHAMAR TORE

(30)Priority

Priority number : 89 8904082

Priority date: 04.12.1989


Priority country: SE

(54) HUB BEARING UNIT

(57)Abstract:

PURPOSE: To minimize influence of inertia force by installing an annular carrier connected to a force sensor as a measuring means in a second ring on the chassis side to a first ring on the wheel side and measuring external force to a wheel by means of the measuring means.

CONSTITUTION: A first ring connected to a wheel and a non-rotatable second ring connected to a chassis are arranged, and a washer 15 in the second ring is fixed to the chassis by means of four bolts penetrating mounting holes 13 respectively. A measuring body 14 having a sensor element detecting external force working on the wheel is arranged in the mounting hole 13. The sensor element, which is a coating layer containing amorphous magnetostrictive material for example, is installed to the measuring body 14 by an adhesive and the like. The four measuring bodies 14 are mounted on a single base and fixed by means of bolts penetrating through holes. As mechanical distortion of the coating layer changes a



magnetic characteristic, this change is measured, and according to its signal, influence of inertial force working on the wheels and a suspension is lowered.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office